920305 mc BARAFF, KOERNER, OLENDER & HOCHBERG, P.C. ATTORNEYS AT LAW 5335 WISCONSIN AVENUE, N.W., SUITE 300 WASHINGTON, D.C. 20015-2003 (202) 686-3200 B. JAY BARAFF ROBERT L. OLENDER March 5, 1992 JAMES A. KOERNER PHILIP R. HOCHBERG AARON P. SHAINIS LEE J. PELTZMAN MARK J. PALCHICK ALAN E. ARONOWITZ

OF COUNSEL ROBERT BENNETT LUBIC

FAX: (202) 686-8282

ORIGINAL

RECEIVED

MAR 5 - 1992

Donna R. Searcy, Secretary Federal Communications Commission 1919 M Street, N. W. Washington, D. C. 20554

Federal Communications Commission Office of the Secretary

Re: BPH-911230MB

Dear Ms. Searcy:

On behalf of ASF Broadcasting Corporation, applicant for a Construction Permit for a new FM broadcast station on Channel 280A at Westerville, Ohio, there is transmitted herewith in triplicate an amendment to the pending application. This amendment is tendered as a matter of right in that it is filed within 30 days of the Public Notice announcing the acceptance of the application for tender.

Should additional information be necessary in connection with this matter, please communicate with this office.

Very truly yours,

Jámes A. Koerner

counsel for

ASF BROADCASTING CORPORATION

Enclosures

EXAMINERS

JAK: jeb\26054.00\MAR05'92.FCC

ORICHIM.

ORIGINAL

BECEIVED

		<u>KEGEIVEI)</u>
<u></u>	<u>, , , , , , , , , , , , , , , , , , , </u>	
•		
		•
J • 1		
·		
L L		
·		
2		
<u> </u>		¥
		4.
	·	- X-
1		
) <u>-</u> -		
)		
<u></u>		

FOR COMMISSION USE ONLY File No. Section V-B - FM BROADCAST ENGINEERING DATA ASB Referral Date Referred by Name of Applicant ASF Broadcasting Corp. Call letters (if issued) is this application being filed in response to a window? If Yes, specify closing date: Purpose of Application: Icheck apprepriate bestes! X Construct a new (main) facility Construct a new auxiliary facility Modify existing construction permit for main facility Modify existing construction permit for auxiliary facility Modify licensed auxiliary facility Modify licensed main facility If purpose is to modify, indicate below the nature of change(s) and specify the file number(s) of the authorizations affected. Antenna supporting-structure height Effective radiated power Antenna height above average terrain Frequency Antenna location Class Main Studio location Other (Semerize briefly) File Number(s) 1. Allocation: Class icheck only one box below? Channel No. Principal community to be served: City County State Franklin OH Westerville 280 2 Exact location of antenna (a) Specify address, city, county and state. If no address, specify distance and bearing relative to the nearest town or landmark 1.5 km SE of Sunbury on St.Rd.37, Delaware Co., OH. Site is 14 km N-NE of Westerville (b) Geographical coordinates (to nearest second). If mounted on element of an AM array, specify coordinates of center of array. Otherwise, specify tower location. Specify South Latitude or East Longitude where applicable; otherwise, North Latitude or West Longitude will be presumed. Latitude Longitude 20 04 82 50 40 14 3. Is the supporting structure the same as that of another station(s) or proposed in another pending application(s)? former WBBY-FM If Yes, give call letter(s) or file number(s) or both. If proposal involves a change in height of an existing structure, specify existing height above ground level including antenna, all other appurtenances, and lighting, if any. DNA

100

10. Is a directional antenna proposed?	X Yes No
If Yes, attach as an Exhibit a statement with all data specified in 47 C.F.R. Section 73.316.	
including plot(s) and tabulations of the relative field.	Exhibit No. E-4
IL Will the proposed facility satisfy the requirements of 47 C.F.R Sections 73.315(a) and (b)?	X Yes No
If No, attach as an Exhibit a request for waiver and justification therefor, including amounts and percentages of population and area that will not receive 3.16 mV/m service.	Exhibit No.
12. Will the main studio be within the protected 316 mV/m field strength contour of this proposal?	X Yes No
If No, attach as an Exhibit Justification pursuant to 47 C.F.R. Section 73.1125.	Exhibit No.
13. (a) Does the proposed facility satisfy the requirements of 47 C.F.R. Section 73.207?	Yes X No
(b) If the answer to (a) is No, does 47 C.F.R. Section 73.213 apply?	Yes X No
(c) If the answer to (b) is Yes, attach as an Exhibit a justification, including a summary of previous waivers.	Exhibit No. DNA
(d) If the answer to (a) is No and the answer to (b) is No, attach as an Exhibit a statement describing the short spacing(s) and how it or they arose.	Exhibit No. Disc.
(e) If authorization pursuant to 47 C.F.R. Section 73.215 is requested, attach as an Exhibit a complete engineering study to establish the lack of prohibited overlap of contours involving affected stations. The engineering study must include the following:	Exhibit No. E-7
(i) Protected and interfering contours, in all directions (660°), for the proposed operation. (2) Protected and interfering contours, over pertinent arcs, of all short-spaced assignments, applications and allotments, including a plot showing each transmitter location, with identifying call letters or file numbers, and indication of whether facility is operating or proposed. For vacant allotments, use the reference coordinates as the transmitter location.	
(3) When necessary to show more detail, an additional allocation study utilizing a map	
with a larger scale to clearly show prohibited overlap will not occur. (4) A scale of kilometers and properly labeled longitude and latitude lines, shown across the entire exhibit(s). Sufficient lines should be shown so that the location of the sites may be verified.	
(5) The official title(s) of the map(s) used in the exhibits(s).	
14. Are there: (a) within 60 meters of the proposed antenna, any proposed or authorized FM or TV transmitters, or any nonbroadcast tescept citizens bend or executive radio stations, or (b) within the blanketing contour, any established commercial or government receiving stations, cable head-end facilities, or populated areas; or (c) within ten (i0) kilometers of the proposed antenna, any proposed or authorized FM or TV transmitters which may produce receiver-induced intermodulation interference?	X Yes No
If Yes, attach as an Exhibit a description of any expected, undesired effects of operations and remedial steps to be pursued if necessary, and a statement accepting full responsibility for the elimination of any objectionable interference (including that caused by receiver-induced or other types of modulation) to facilities in existence or authorized or to radio receivers in use	Exhibit No.

prior to grant of this application. (See 47 C.F.A. Sections 73.315(b), 73.316(e) and 73.318.)

15. Attach as an Exhibit a 75 minute series U.S. Geological Survey topographic quadrangle map that shows clearly, legibly, and accurately, the location of the proposed transmitting antenna. This map must comply with the requirements set forth in Instruction V. The map must further clearly and legibly display the original printed contour lines and data as well as latitude and longitude markings, and must bear a scale of distance in kilometers. Exhibit No. E-5

16. Attach as an Exhibit these the secret a map which shows clearly, legibly, and accurately, and with the original printed latitude and longitude markings and a scale of distance in

Exhibit No.

	Height of radiation center above average	Predicted Distances			
Radial bearing (degrees True)	elevation of radial from 8 to 18 km (meters)	To the 3.16 mV/m contour (kilometers)	To the 1 mV/m contour (kilometers)		
* 212	148.1	19.0	32.4		
0	96.0	10.0	17.9		
4 5	68.0	11.4	20.4		
90	76.4	13.4	23.9		
136	90.7	14.5	25.9		
180	116.5	16.8	29.1		
225	144.7	18.8	32.0		
270	143.1	17.2	29.6		
316	136.7	12.1	21.9		

^{*}Radial through principal community, if not one of the major radials. This radial should NOT be included in the calculation of HAAT.

20	Environmental	Statement/See	47 [5]	Section 1	1101 at sag	1

Would a Commission grant of this appli that it may have a significant environ		n 1.1907 of the FCC Rules,	, such Yes X No
If you answer Yes, submit as an Exhibit	an Environmental Assess	ment required by Section	n LISIL Exhibit No.
does <u>not</u> high inter (requency	cation meets the requirements of Commental processing pursuant to Sell involve a site location specifisity lighting under Section 1.1307 radiation in excess of the application's Rules.	ection 1.1306 of the Commission's led under Section 1.1307(a)(1)-(! 7(a)(6): or, (3) result in human	# Rules, because it 5); [2] involve exposure to radio

CERTFICATION

I certify that I have prepared this Section of this application on behalf of the applicant, and that after such preparation. I have examined the foregoing and found it to be accurate and true to the best of my knowledge and belief.

Name (Typed or Printed)	Relationship to Applicant (e.g., Consulting Engineer)		
E. Harold Munn, Jr. & Associates, Inc.	Technical Consultant		
Signature Mull Muny	Address (Include 217 Code) Box 220 Coldwater, MI. 49036		
Date / O	Telephone No. linciple Area Codel		
February 17, 1992	(517) 278-7339		

ENGINEERING REPORT

NEW FM BROADCAST STATION

CHANNEL 280(A)

WESTERVILLE, OHIO

February, 1992

PREPARED BY:

E. HAROLD MUNN, JR. & ASSOCIATES, INC.

ONE HUNDRED AIRPORT ROAD

COLDWATER, MICHIGAN 49036

(517) 278-7339

TABLE OF CONTENTS

- 1. Table of Contents
- 2. Certification of Engineer
- 3. Discussion of Report
- 4. Exhibit A Acceptance of Responsibility for Interference Correction
- 5. Exhibit E-1 Proposed Service Contour Study
- 6. Exhibit E-2 Topographic Data Employed in Application
- 7. Exhibit E-3 Vertical Plan of Antenna System and Support Tower
- 8. Exhibit E-4 Tabulation of Operating Conditions
- 9. Exhibit E-5 Portion of Topographic Map Showing Site
- 10. Exhibit E-5A Portion of Aero Chart Showing Site
- 11. Exhibit E-6 Tabulation of Population and Area Served
- 12. Exhibit E-7 Request for Processing Under Section 73.215

E. HARDLD MUNN, JR. & ASSOCIATES, INC. Broadcast Engineering Consultants Coldwater, Michigan

CERTIFICATION OF CONSULTANT

The firm of E. Harold Munn, Jr. & Associates, Inc., Broadcast Engineering Consultants, with offices at 100 Airport Drive, Coldwater, Michigan, has been retained for the purpose of preparing the technical data forming this report.

The report has been prepared by properly trained electronics specialists under the direction of the undersigned whose qualifications are a matter of record before the Federal Communications Commission.

I declare under penalty of perjury that the contents of this report are true and accurate to the best of my knowledge and belief.

E. HAROLD MUNN, JR. & ASSOCIATES, INC.

February 17, 1992

E. Harold Munn, Jr //President

100 Airport Drive, Box 220 Coldwater, Michigan 49036

(517) 278-7339

DISCUSSION


This firm was retained to prepare the required engineering report in support of an application for a new FM Broadcast Station, serving the area of Westerville, Ohio. FM Channel 280, 103.9 mHz, is listed in the Table of Allotments for use at Westerville, as a Class A channel. This application proposes the use of that channel, at the former transmitter site of WBBY-FM.

The proposed service contours have been calculated in accordance with the Rules, and the data obtained has been tabulated and plotted in this report. The plotted contours are found as Exhibit E-1 of this report. This exhibit shows the 3.16 mV/m contour which serves the community of license, and the overall service which is provided by the 1.0 mV/m contour of the facility.

The remainder of the information in this report is responsive to the Rules of the Commission, and provides the data for F.C.C. Form 301, Section V-B.

The antenna height above average terrain has been calculated using the NGDC 30" topographic database.

This application meets the spacing requirements of the Rules, Section 73.207(b)(1)Table A concerning United States stations and allotments with one exception. Processing under Section 73.215 of the Rules is requested, and the allocation details are included as Exhibit E-7 of this report. Protection to the short-spaced station will be



ENVIRONMENTAL ASSESSMENT

The FM Broadcast facility proposed in the referenced application will not result in human exposure to radiofrequency radiation in excess of the applicable safety standards specified in Section 1.1307(b) of the Commission's rules.

RADIATION PROTECTION: This proposal has been evaluated for compliance with FCC guidelines concerning human exposure to radio-frequency radiation. The standards employed are detailed in OST Bulletin No. 65, October, 1985.

Table 1 of Appendix B was employed for this study concerning FM broadcast radiation protection.

For the effective radiated power and type of antenna proposed, the minimum antenna radiation center above ground is specified as 18.3 meters.

This application proposes an antenna height above ground of at least 110 meters. Therefore, full compliance with the guidelines is attained by the instant application.


In addition to the protection afforded by the proposed antenna height above ground, the facility will be properly marked with signs. and entry to the facility will be restricted by means


EXHIBIT "A"

The transmitting facility is so located that there is some resident population within the predicted "blanketing" contour, as defined in 47 C.F.R. 73.318. The applicant agrees that full compliance with the procedures and requirements of 73.318(b)(d) will be attained.

The applicant will take such engineering steps as may be required to satisfy complaints of "blanketing" including, but not limited to, the installation of filters, traps, or other devices to satisfy said complaints within the specified time period.

This applicant accepts full responsibility for the <u>elimination</u> of any objectionable interference.





ANALYSIS OF TOPOGRAPHIC DATA EMPLOYED

The topographic data employed in this application is based on the National Geophysical Center thirty second point topography data base (TPG-0050).

The averages calculated include 130 points between 3 and $16\ km$.

The transmitter site elevation was determined by means of 7.5' series topographic mapping. The site coordinates were also developed from the 7.5' series map.

A portion of that map is included in this report as Exhibit E-5.

A detailed topographic analysis using 7.5' topographic maps will be supplied to the Commission if requested.

E. HARDLD MUNN, JR. & ASSOCIATES, INC. Broadcast Engineering Consultants Coldwater, Michigan



PROPOSED FM OPERATING SPECIFICATIONS

Applicant: ASF Broadcasting Corp.

Max.

Frequency: 103.9 mHz Channel: 280(A) ERP: DA 5 kW HAAT: 109 (meters)

Transmitter Location: 1.5 km SE of Sunbury on St. Rd. 37, 14 km N-NE of

Westerville, Ohio (Westerville in Franklin Co.)

County: Delaware

State: Ohio

Site Coordinates: NL 40°14'04"; WL 82°50'20" Site Elevation: 311 meters

Proposed Operation:

Effective Radiated Power: 5 (kW)H 5 kW(V) (maximum DA ERP)

Height of Antenna Radiation Center Above:

	Average Te	Mean Sea Level		Gnd.		
Н	109	meters	421	m	110	m
v	109	meters	421	m	110	m

Overall Height of Structure Above Ground: 124 meters Overall Height of Structure Above Mean Sea Level: 435 meters


COMPLIANCE WITH 47 C.F.R. Sec. 73.316(c)(5)(6)(7)(8)

The antenna proposed in this application will be mounted in accordance with specific instructions provided by the antenna manufacturer. The antenna will be tested by the manufacturer using the type of mounting which will be employed in the field.

No other antennae of any type are or will be mounted on the same tower level as the directional antenna.

No antenna of any type is or will be mounted within any horizontal or vertical distance specified by the antenna manufacturer as being necessary for proper directional operation.

Upon completion of antenna construction, a statement from a licensed surveyor will be submitted with the application for license. This statement will certify that




DIRECTIONAL ANTENNA RELATIVE FIELD

PATTERN AZIMUTH: 0° = 160 °T.

HTUMISA	FIELD	AZIMUTH	FIELD
0 °	1.000	180°	0.400
10°	1.000	190°	0.400
20°	1.000	200°	0.435
30°	1.000	210°	0.480
40°	1.000	220°	0.550
45°	1.000	225°	0.595
50°	1.000	230°	0.640
60°	1.000	240°	0.750
70°	1.000	250°	0.860
80°	1.000	260°	0.950
90°	0.990	270°	0.990
100°	0.950	280°	1.000
110°	0.860	290°	1.000
120°	0.750	300°	1.000
130°	0.640	310°	1.000
135°	0.595	315°	1.000
140°	0.550	320°	1.000
150°	0.480	330°	1.000
160°	0.435	340°	1.000
170°	0.400	350°	1.000

E. HARDLD MUNN, JR. & ASSDCIATES, INC. Broadcast Engineering Consultants
Coldwater, Michigan



PROGRAM NO. FMP

ELEVATION PATTERN DATE: FEBRUARY 17, 1992 BEAM TILT= 0% JSCP-3(DA) - 3RMS GAIN= 3 NULL FILL= 0% PLOT PREPARED FOR: ASF BROADCASTING FREO: 103.9 mHz .1 . 3 . 6 ELEVATION FIELD . 2 . 4 . 5 . 7 . 8 . 9 1.0 :*---+--20.00 .024 * 17.50 .120 15.00 .285 .459 12.50 : 10.00 .629 7.50 .779 5.00 .898 2.50 .974 0.00 1.000 .974 -2.50-5.00 .898 .779 -7.50 -10.00 .629 .459 -12.50-15.00 .285 -17.50.120 : -20.00 .024 ; * -22.50 .139 -25.00 .219 -27.50 .262 .271 -30.00 -32.50 .248 -35.00 .201 -37.50.136 .062 -40.00 : : * -42.50.016 -45.00 .091 -47.50 .158 .216 -50.00 -52.50 .261 .294 -55.00 -57.50 .314 .324 -60.00 -62.50 .324 -65.00 .317 -67.50.304 -70.00 .286 -72.50.266 .245 -75.00-77.50 .223 .201 -80.00 -82.50 .180 -85.00 .161 -87.50 .142 -90.00 .125

RF SPECIALTIES

Predicted Signal Contours: Major Lobe Orientation 160° T.

40 14 04 - WESTERVILLE OHIO

82 50 20 - DIRECTIONAL PATTERN CONTOURS

ERP = 5 Radial	kW, 6.99 dBk HAAT	FM -	2-6 Tabl	les Field	70 dBu.5	60 dBu.5
0 Degs	. 96.0M	0.946	-0.241	0.435	10.0	17.9
10 Degs		1.152	0.615	0.480	10.2	18.3
20 Degs	. 84.6M	1.513	1.797	0.550	10.5	18.9
30 Degs	. 77.4M	2.048	3.113	0.640	10.9	19.5
40 Degs	. 70.3M	2.813	4.491	0.750	11.2	20.1
50 Degs	. 69.3M	3.698	5.680	0.860	11.9	21.3
60 Degs	. 68.5M	4.512	6.544	0.950	12.4	22.2
70 Degs		4.901	6.902	0.990	12.7	22.8
80 Degs		5.000	6.990	1.000	13.0	23.3
90 Degs		5.000	6.990	1.000	13.4	23.9
100 Degs		5.000	6.990	1.000	13.5	24.1
110 Degs		5.000	6.990	1.000	13.7	24.6
120 Degs		5.000	6.990	1.000	14.2	25.4
130 Degs		5.000	6.990	1.000	14.5	25.9
140 Degs		5.000	6.990	1.000	14.5	25.9
150 Degs		5.000	6.990	1.000	14.7	26.2
160 Degs		5.000	6.990	1.000	15.1	26.8
170 Degs		5.000	6.990	1.000	16.1	28.2
180 Degs		5.000	6.990	1.000	16.8	29.1
190 Degs		5.000	6.990	1.000	17.3	29.8
200 Degs		5.000	6.990	1.000	18.7	31.8
210 Degs		5.000	6.990	1.000	19.0	32.3
220 Degs		5.000	6.990	1.000	18.8	32.1
230 Degs		5.000	6.990	1.000	18.7	31.9
240 Degs		5.000	6.990	1.000	18.5	31.5
250 Degs		4.901	6.902	0.990	18.3	31.3
260 Degs		4.512	6.544	0.950	18.0	30.8
270 Degs		3.698	5.680	0.860	17.2	29.6
280 Degs 290 Degs		2.813	4.491	0.750	16.0	27.9 25.9
-		2.048	3.113	0.640	14.6	24.0
300 Degs 310 Degs		1.513 1.152	1.797 0.615	0.550 0.480	13.4 12.4	22.4
320 Degs		0.946	-0.241	0.435	11.8	21.3
330 Degs		0.800	-0.969	0.400	11.0	20.0
_	. 118.5M					
	. 112.2M					
					10.5	10.7
	T= 109.4M,	Ant. COR	= 420.6M	AMSL		
	. 68.0M					
	. 90.7M					
212 Degs	. 148.1M	5.000	6.990	1.000	19.0	
	. 144.7M					32.0
315 Degs	. 136.7M					21.9

UNITED STATES
DEPARTMENT OF THE INTERIOR EXHIBIT E-5 (PA.



TABULATION OF POPULATION AND AREA

CONTOUR

POPULATION

<u>AREA</u>

1.0 mV/m

604,037

2,048 km²

